



Quick coupling with manometer :
Female 2" - Male 1 1/2"
Female 2" - Male 2"



FEATURES

- ✓ Aluminium and metal body gun
- ✓ Full circle and part circle
- ✓ Trajectory angle : 25°
- ✓ Slow return
- ✓ Inlet : 2" BSP female
- ✓ Size nozzle : Ø10 to Ø22 mm
- ✓ Discharge from 6.5 to 48.5 m³/h
- ✓ Radius from 19 to 46 meters
- ✓ Working pressure : 2 to 7 bars
- ✓ Weight : 5.3 Kg

USE

- Cooling of synthetic turf.
- Landscape application, natural and synthetic turf, golf courses, Horse racing fields, ...

SPECIALITIES

- Small and compact design.
- Suitable for use in confined working space.
- Nice uniform distribution.
- Suitable for portable and fixed systems.

YK32 (full circle or part circle)

Nozzle size (mm)	Pressure (bar)	Discharge (m ³ /h)	Radius* (m)	Pluviometry mm/h*	Cycle times (min.)
10	2	6,5	19	5,7	
	3	7,5	21	5,4	
	4	8,6	23	5,2	
12	2	8,4	21	6,1	
	3	9,9	25	5,0	
	4	11,5	28	4,7	
14	3	14,3	28	5,8	2,46
	4	17	30	6,0	2,24
	5	18,2	32	5,7	2,04
16	3	18,2	30	6,4	
	4	21,1	33	6,2	
	5	23,5	35	6,1	
18	3	22	31	7,3	2,50
	4	26,3	34	7,2	2,32
	5	29,5	37	6,9	2,10
	6	32,2	38	7,1	2,04
20	3	27	34	7,4	
	4	31,5	37	7,3	
	5	36	40	7,2	
22	4	38	37	8,8	
	5	42	40	8,4	
	6	44	43	7,6	
	7	48,5	46	7,3	

* To be used for informational purpose only.

