



Quick coupling with manometer :  
Female 2" - Male 1 1/2"  
Female 2" - Male 2"



### FEATURES

- ✓ Aluminium and metal body gun
- ✓ Full circle and part circle
- ✓ Trajectory angle : 25°
- ✓ Slow return
- ✓ Inlet : 2" BSP female
- ✓ Size nozzle : Ø14 to Ø24 mm
- ✓ Discharge from 14.8 to 61.2 m³/h
- ✓ Radius from 29 to 50 meters
- ✓ Working pressure : 2 to 7 bars
- ✓ Weight : 7 Kg

### USE

- Overhead irrigation for agricultural crop : corn, potatoes, wheat, clover, ...
- Landscape application, sport field, mines, horse racing fields.

### SPECIALITIES

- Nice uniform distribution.
- Makes full and semi-circle turns at the same speed.
- Evenness and lightness of watering.
- Delivered with 4 nozzles.
- Suitable for portable and fixed systems.

### YK50 (Full circle or part circle)

Nozzle size (mm)	Pressure (bar)	Discharge* (m3/h)	Radius* (m)	Pluviometry mm/h*
14	3.0	14.8	29	5,6
	4.0	17.2	32	5,3
	5.0	18.9	34	5,2
16	3.0	18.5	30	6,5
	4.0	21.5	34	5,9
	5.0	23.5	35	6,1
18	3.0	23.4	32	7,3
	4.0	26.7	35	6,9
	5.0	29.9	38	6,9
	6.0	33.2	41	6,3
20	3.0	27.8	35	7,2
	4.0	32.9	38	7,3
	5.0	37.0	42	6,7
22	4.0	40.8	40	8,1
	5.0	45.2	44	7,4
	6.0	49.1	47	7,1
24	5.0	53.2	46	8,0
	6.0	57.5	48	7,9
	7.0	61.2	50	7,8

\* To be used for informational purposes only.

