



Quick coupling with manometer :  
Female 2" - Male 1 1/2"  
Female 2" - Male 2"

## FEATURES

- ✓ Aluminium and metal body gun
- ✓ Full circle and part circle
- ✓ Trajectory angle : 25°
- ✓ Slow return
- ✓ Inlet : 2" BSP female
- ✓ Size nozzle : Ø14 to Ø24 mm
- ✓ Discharge from 13.2 to 57 m<sup>3</sup>/h
- ✓ Radius from 24 to 50 meters
- ✓ Working pressure : 2 to 7 bars
- ✓ Weight : 7 Kg

## YK50T (Full circle and part circle)

Nozzle size (mm)	Pressure (bar)	Discharge* (m <sup>3</sup> /h)	Radius* (m)	Pluviometry mm/h*
14	2.5	13.2	24	7,3
	3.0	14.0	26	6,6
	4.0	16.2	29	6,1
16	2.0	14.5	26	6,8
	3.0	17.8	29	6,7
	4.0	20.5	31	7,0
	5.0	23.2	33	6,8
18	3.0	22.5	32	7,0
	4.0	26.3	35	6,8
	5.0	28.2	37	6,6
20	6.0	31.3	40	6,2
	3.0	26.7	35	6,9
22	4.0	32.2	37	7,5
	5.0	35.5	42	6,4
	4.0	33.4	35	8,7
24	5.0	38.5	37	9,0
	6.0	43.0	40	8,6
	4.0	46.3	43	8,0
	5.0	48.1	45	7,6
	6.0	53.1	47	7,7
	7.0	57.0	50	7,3

\* To be used for informational purpose only.

## USE

- Irrigation with dirty or charged water.
- All types of field crop : corn, potatoes, wheat, clover, ...
- Industrial use of any kind

## SPECIALITIES

- Special rubber nozzle which automatically expand in case of clogging to dilute and distribute manures.
- Single nozzle for limiting the risks of obstructions.
- Delivery with 4 nozzle.
- Suitable for portable and fixed systems.

