



Quick coupling with manometer :  
Female 2" - Male 1 1/2"  
Female 2" - Male 2"

## FEATURES

- ✓ Aluminium and metal body gun
- ✓ Full circle and part circle
- ✓ Trajectory angle : 25°
- ✓ Slow return
- ✓ Inlet : 2,5" BSP female
- ✓ Size nozzle : Ø20 to Ø32 mm
- ✓ Discharge from 28 to 108.84 m³/h
- ✓ Radius from 34 to 66 meters
- ✓ Working pressure : 3 to 7 bars
- ✓ Weight : 9 Kg

## USE

- The multifaceted model in the range. It is widely used for field crops such as corn, sugar beet, potato, alfalfa, wheat, etc.
- Appropriate for all Agricultural and Industrial applications.

## SPECIALITIES

- Nice uniform distribution.
- Makes full and semi-circle turns at the same speed.
- Delivery with 4 nozzle.
- Long range

## YK65 (Full circle and part circle)

Nozzle size (mm)	Pressure (bar)	Discharge* (m3/h)	Radius* (m)	Pluvimetry mm/h*
20	3.0	28	34	7.2
	4.0	33	38	7.3
	5.0	37	42	6.7
22	3.0	34	37	7.5
	4.0	41	40	8.1
	5.0	45	44	7.4
24	6.0	49	47	7.1
	4.0	43.74	43	7.5
	5.0	48.90	49	6.5
26	6.0	53.58	52	6.3
	3.0	51.36	49	6.8
	4.0	57.42	50	7.3
28	5.0	62.88	54	6.9
	4.0	59.52	51	7.3
	5.0	66.54	55	7.0
30	6.0	72.9	58	6.9
	5.0	73.32	56	7.4
	6.0	83.58	62	6.9
32	7.0	90.3	64	7.0
	4.0	86.94	62	7.2
	5.0	95.22	64	7.4
	6.0	108.84	66	8.0

\* To be used for informational purpose only.

